



Contact Rubber

# DURAGRIP COMPOUND



**PULLER / HAUL-OFF BELTS**  
**RUBBER COMPOUND SPECIFICALLY DESIGNED FOR THE**  
**EXTRUSION INDUSTRY**

**DURAGRIP** was specifically designed to meet the needs of plastic extruders. Our clients are known to serve a variety of industries such as **tubing/piping, windows and doors, decking, fencing and many more.**

The **DURAGRIP** blend will improve your wear resistance while maximizing your grip. The overall performance of **DURAGRIP** belts is second to none.

## TECHNICAL DATA

PROPERTIES	DURAGRIP	EPDM	PURE GUM
Tensile P.S.I	3300	2100	3200
Elongation %	650	570	610
Temperature (°F)	250	320	175
Abrasion (g/1000 rev.)	0.187	0.230	0.710

## DURAGRIP FEATURES:

- Maximum grip (High Coefficient of Friction)
- Excellent abrasion resistance
- Seamless
- Vulcanized
- Multidirectional
- Non-marking compound



**Contact Rubber**

2227, 46<sup>th</sup> Ave., Lachine, Québec, Canada H8T 3C9  
T.: +1.514. 631-0234 E.: info@ctcrubber.com

[ctcrubber.com](http://ctcrubber.com)